



# SLC CUBE3+ Uninterruptible power supply system from 7.5 to 200 kVA

## SLC CUBE3+: Energy efficiency with superior electrical protection

Salicru's **SLC CUBE3+** series is a UPS range featuring high-performance, On-line double conversion (VFI) technology that provides a reliable, high-quality power supply and, at the same time, achieves significant energy and financial savings in terms of installation and operating costs.

Particularly noteworthy is the unit's input power factor (PF=1) and its extremely low distortion rate (THDi even lower than 1%), which help to reduce installation and operating costs, and contribute to improving the quality of the electrical network.

The output power factor (PF=0.9) also stands out, providing optimum electrical protection for computer systems and low harmonic output distortion (THDv even lower than 0.5%), enabling it to protect any type of load (inductive, resistive, capacitive or mixed). In addition, the performance achieved (up to 95% in On-line mode and 98% in Smart Eco-mode) produces significant energy consumption savings and reduces air conditioning needs.

For a full optimum solution, the **SLC CUBE3+** provides maximum adaptability (even with the standard model), the possibility of parallel redundant expansion and extensive communication options. Finally, also worth noting is the unit's lightweight design and reduced dimensions, enabling it to be easily installed and ensuring that footprint is minimal.

## Performances

- On-line double conversion (VFI) technology with DSP control.
- Input power factor 1, for better performance.
- Very low input current harmonic distortion (THDi as low as <1%).
- Total flexibility in input/output voltage. <sup>(1)</sup>
- Designed to withstand any type of load.
- Batt-Watch function for monitoring and battery care.
- High output power factor (PF=0.9). <sup>(2)</sup>
- Very low output voltage distortion rate (THDv even lower than 0.5%).
- On-line mode efficiency of up to 95%.
- Smart Eco-mode efficiency of up to 98%.
- Very compact design with minimal footprint.
- Can be integrated into the most advanced IT environments.
- Parallel redundant configuration (N+1) for critical installations. <sup>(3)</sup>
- Built with 80% recyclable materials.
- Bluetooth application display for Android (up to 10 m).
- SLC Greenergy solution.

(1) Single/single, single/three and three/single configurations up to 60 kVA  
 (2) Up to 120 kVA  
 (3) Up to 4 units



SLC CUBE3 +




## Applications: Designed to protect any type of environment

High-end design features plus great flexibility capacity (options, power upgrading, communications, ...) make **SLC CUBE3+** series the best option to protect and secure a wide range of environments: data-centres, hosting, housing, IT-networks, server farms, voice and data networks,...


## High efficiency

High performance in On-line and Smart Eco-mode operation.



## Low harmonic distortion

The lowest harmonic distortion in the market.



## Options

- Ethernet/SNMP adapter or GPRS modem.
- SICRES adapter for remote management.
- Android wireless link.
- Monitoring, management and shutdown software.
- 1 x additional RS-232/485 serial port.
- Extended backup times.
- Common battery set for parallel systems.
- BACS II, battery monitoring, regulation and alarms.
- Dual-level charger for NiCd batteries.
- Separate bypass line.
- Single/single, single/three and three/single configurations.<sup>(1)</sup>
- External manual bypass.
- Temperature and humidity sensors.
- External display.
- Frequency converter function.

(1) Up to 60 kVA

## Technical support and service

- Pre and post-sales advice.
- Start-up.
- Telephone technical support.
- Preventative/corrective intervention.
- Maintenance contracts.
- SICRES remote maintenance contracts.
- Training courses.

# SLC CUBE3+



Uninterruptible power supply system from 7.5 to 200 kVA

## TECHNICAL SPECIFICATIONS

MODEL		SLC CUBE3+
TECHNOLOGY		On-line, double conversion, HF, DSP control
INPUT	Nominal voltage <sup>(1)</sup>	Single-phase 120 / 127 / 220 / 230 / 240 V Three-phase 3 x 208 / 3 x 220 / 3 x 380 / 3 x 400 / 3 x 415 V (3P + N)
	Voltage margin	+15% / -20% (configurable)
	Frequency	50 / 60 Hz
	Total Harmonic Distortion (THDi)	7.5 ÷ 20 kVA: 100% load: <1.5% / 50% load: <2.5% / 10% load: <6.0% 30 ÷ 80 kVA: 100% load: <1.0% / 50% load: <2.0% / 10% load: <5.0% 100 ÷ 200 kVA: 100% load: <1.5% / 50% load: <2.0% / 10% load: <6.0%
	Power factor	>1 from 10% load
	Rectifier topology	Three-phase IGBT full wave, soft start, PFC, transformerless
	OUTPUT	Nominal voltage <sup>(1)</sup>
Accuracy	State	± 1% steady / ± 2% dynamic
	Response time	20 ms for load steps 0% ÷ 100% and voltage drop up to -5%
Frequency	Synchronised	50/60 Hz ±5 Hz (selectable)
	Free running	50/60 Hz ±0.05%
Maximum synchronisation speed	From 1 Hz/s to 10 Hz/s (programmable)	
Total Harmonic Distortion (THDv)	Linear load	<0.5%
	Nonlinear load	7.5 ÷ 80 kVA: <1.5% / 100 ÷ 200 kVA: <2% (EN-62040-3)
Output Power Factor <sup>(2)</sup>	0.9	
Admissible overload	125% for 10 min / 150% for 60 s	
Admissible crest factor	>3:1	
Total efficiency in On-line mode	7.5÷60 kVA: 92.0%÷93.0% / 80÷200 kVA: 94.0%÷95.0%	
Efficiency in Smart Eco-mode	Up to 98,4%	
STATIC BYPASS	Type and activation criteria	Solid state, controlled by microprocessor
Transfer time	On-line mode	Nil
	Smart Eco-mode	4 ms (typical)
	Transfer to bypass	Immediate, for overloads exceeding 150%
Retransfer	Automatic, after alarm deactivation	
MANUAL BYPASS	Type	Without interruption
BATTERIES	Type (standard)	Lead acid, sealed, maintenance free
	Charge voltage regulation	Batt-Watch
COMMUNICATION	Ports	1 x RS-232/485, with MODBUS protocol
	Interface to relays	4 x AC failure, bypass, low battery and general
	Free slots	1, for SNMP/SICRES
	Parallel connection	2 x connectors
GENERAL	Operating temperature	0° C ÷ +40° C
	Relative humidity	Up to 95%, non-condensing
	Operating altitude	1,000 masl
	Acoustic noise at 1 metre	<52 dB(A) <sup>(3)</sup>
STANDARDS	Safety	EN-62040-1-2; EN-60950-1
	Electromagnetic Compatibility (EMC)	EN-62040-2
	Operating	VFI-SS-111 according to EN 62040-3
	Quality and Environmental Management	ISO 9001 and ISO 14001

(1) Single-phase 120 / 127 V available up to 30 kVA inclusive and three-phase 3 x 208 / 3 x 220 V available up to 100 kVA inclusive.

(2) Up to 120 kVA inclusive at three/three-phase configurations.

(3) <65 dB(A) for 80 to 120 kVA models / <70 dB(A) for 160 and 200 kVA models.

Information subject to change without notice.

## RANGE

MODEL	POWER (kVA / kW)	N° CABINETS (UPS + BAT)	UPS DIMENSIONS (D x W x H mm)	WEIGHT (kg)	BAT DIMENSIONS (D x W x H mm)	WEIGHT (kg)
SLC-7.5-CUBE3+	7.5 / 6.75	1 + 0	775 x 450 x 1100	207	-	-
SLC-10-CUBE3+	10 / 9	1 + 0	775 x 450 x 1100	207	-	-
SLC-15-CUBE3+	15 / 13.5	1 + 0	775 x 450 x 1100	209	-	-
SLC-20-CUBE3+	20 / 18	1 + 0	775 x 450 x 1100	235	-	-
SLC-30-CUBE3+	30 / 27	1 + 0	775 x 450 x 1100	319	-	-
SLC-40-CUBE3+	40 / 36	1 + 0	775 x 450 x 1100	417	-	-
SLC-50-CUBE3+	50 / 45	1 + 1	775 x 450 x 1100	185	775 x 450 x 1100	321
SLC-60-CUBE3+	60 / 54	1 + 1	775 x 450 x 1100	185	775 x 450 x 1100	551
SLC-80-CUBE3+	80 / 72	1 + 1	880 x 590 x 1325	265	1050 x 650 x 1325	1020
SLC-100-CUBE3+	100 / 90	1 + 1	880 x 590 x 1325	290	1050 x 650 x 1325	1020
SLC-120-CUBE3+	120 / 108	1 + 1	880 x 590 x 1325	290	1050 x 650 x 1325	1020
SLC-160-CUBE3+	160 / 128	1 + 1	850 x 900 x 1905	540	850 x 1305 x 1905	1655
SLC-200-CUBE3+	200 / 160	1 + 1	850 x 900 x 1905	550	850 x 1305 x 1905	1690

Nomenclature, dimensions and weights for units with input voltage 3 x 400 V, output voltage 3 x 400 V and standard backup time.



@salicru\_SA



www.linkedin.com/company/salicru

(\*) Spain only (\*\*) Rest of the world

902 48 24 00\* +34 93 848 24 00\*\* WWW.SALICRU.COM

AVDA. DE LA SERRA 100 · 08460 PALAUTORDERA (SPAIN) · FAX +34 93 848 11 51 · salicru@salicru.com

# SALICRU